

No. 1304 Stainless steel sheaves

made of grade 1.4301 stainless steel, turned groove, with sealed ball bearings.
All dimensions in mm.



Sheave external Ø	50	75	100	125	150
Groove base Ø	38	59	80	103	126
Groove radius	3.2	4.2	4.8	5.3	6.5
Groove depth	6	8	10	11	12
Rim width	12	18	21	21	22
Bore for bolt	10	12	15	20	20
Hub length	16	20	25	25	25
Hub Ø	29	36	42	48	56
Rope Ø max.	6	8	9	10	12
Ball bearing type	6000-2RS1	6001-2RS1	6002-2RS1	6004-2RS1	6004-2RS1
Load capacity in kg	100	200	300	500	750
Weight in kg approx.	0.10	0.30	0.60	0.90	1.40

No. 1305 Stainless steel sheaves

made of grade 1.4571 stainless steel (V4A), turned groove, with sealed ball bearings.
All dimensions in mm.



Sheave external Ø	85	125	180	240	300	360
Groove base Ø	60	90	135	185	230	280
Groove radius	3.2	4.8	7	9.5	12.5	15
Groove depth	12	17	22	27	35	40
Rim width	21	30	38	50	60	70
Bore for bolt	12	20	25	35	45	60
Hub length	17.5	30	33	45	54	67
Hub Ø	40	65	75	110	130	170
Rope Ø max.	6	9	13	18	23	27
Ball bearing type	6001-2RS	6204-2RS	6205-2RS	6307-2RS	6309-2RS	6312-2RS
Load capacity in kg	500	1000	2000	4000	6400	10000
Weight in kg approx.	0.70	1.90	5.40	12.80	24.00	40.00