

No. 18 Gin blocks

with steel cross bar and rotating load hook with safety latch, black cathodic dip coated.
The blocks are equipped with cast iron sheaves No. 19 with drilled shaft hole, untreated groove.
All dimensions in mm.



	120	140	160	190	220	250	300
Sheave external Ø	120	140	160	190	220	250	300
Groove base Ø	82	98	116	144	174	202	244
Axle length	75	75	75	90	90	90	90
Total length	230	245	272	320	350	380	430
Total width	170	190	210	250	280	320	350
Hook jaw width	25	25	25	25	25	25	25
Rope Ø max.	22	25	25	28	28	29	30
Load capacity in kg	150	150	200	200	250	250	300
Weight in kg approx.	1.45	1.75	2.05	3.50	4.40	4.30	5.90

Replacement sheaves for gin blocks No. 18

No. 19 Lightweight rope sheaves made of cast iron

untreated groove, drilled shaft hole, with curved spokes, compatible with gin blocks No. 18.
All dimensions in mm.



	120	140	160	190	220	250	300
Sheave external Ø	120	140	160	190	220	250	300
Groove base Ø	82	98	116	144	174	202	244
Groove radius	12	13	13	14.5	14.5	15	16
Groove depth	19	21	22	23	23	24	28
Rim width	35	38	38	43	43	43	47
Bore for bolt	13	13	13	16	16	16	16
Hub length	42	45	46	52	52	52	52
Hub Ø	33	33	35	38	40	40	50
Rope Ø max.	22	25	25	28	28	29	30
Load capacity in kg	150	150	200	200	250	250	300
Weight in kg approx.	0.70	1.00	1.35	1.90	2.40	2.80	4.20