

No. 22 Heavy gin or loading blocks for wire rope

with steel cross bar and rotating load hook, previously DIN 688 or DIN 15401 with safety latch, painted grey-blue. The blocks are equipped with cast iron sheaves No. 23 with drilled shaft hole, turned groove. Only at 310 mm sheave \varnothing the groove is untreated. Also available with swivel oval eye (part no. 22 ö) or with roller bearing (version "W"). All dimensions in mm.



| Sheave external \varnothing | 115 | 155 | 185 | 220 | 260 | 310 |
|-------------------------------|------|------|------|------|-------|-------|
| Groove base \varnothing | 89 | 129 | 149 | 184 | 222 | 250 |
| Axle length | 55 | 62 | 73 | 73 | 80 | 100 |
| Total length | 300 | 350 | 410 | 460 | 520 | 640 |
| Total width | 150 | 192 | 225 | 260 | 280 | 400 |
| Hook jaw width | 30 | 37 | 37 | 40 | 40 | 55 |
| Rope \varnothing max. | 10 | 10 | 16 | 16 | 18 | 26 |
| Load capacity in kg | 500 | 1000 | 1500 | 2000 | 3000 | 5000 |
| Weight in kg approx. | 2.50 | 3.50 | 6.00 | 7.50 | 11.00 | 24.00 |

Replacement sheaves for gin or loading blocks No. 22

No. 23 Wire rope sheaves made of cast iron

Turned groove, drilled shaft hole, compatible with gin blocks and loading blocks No. 22 and with wire rope guide pulleys No. 829. Also available with red brass bushing (version "R") or roller bearing (version "W"). All dimensions in mm.



| Sheave external \varnothing | 115 | 155 | 220 | 260 | 310 |
|-------------------------------|------|------|------|------|-------|
| Groove base \varnothing | 89 | 129 | 184 | 222 | 250 |
| Groove radius | 5.5 | 5.5 | 8.5 | 9.5 | 14 |
| Groove depth | 13 | 13 | 18 | 19 | 30 |
| Rim width | 24 | 27 | 32 | 40 | 52 |
| Bore for bolt | 14 | 19 | 22 | 25 | 35 |
| Hub length | 26 | 28 | 35 | 43 | 56 |
| Hub \varnothing | 36 | 48 | 54 | 65 | 85 |
| Rope \varnothing max. | 10 | 10 | 16 | 18 | 26 |
| Load capacity in kg | 500 | 1000 | 2000 | 3000 | 5000 |
| Weight in kg approx. | 0.90 | 1.40 | 3.30 | 5.20 | 10.00 |