

No. 503 Zinc-plated wire rope thimbles

to DIN 6899 BF.

All dimensions in mm.



Groove width for rope Ø	3	4	5	6	8	10	12
	2.5	3.5	4	5	7	9	11
Internal width	12	13	14	16	20	24	28
Internal height	19	21	23	25	32	38	45
Total length	29	30	33	39	58	59	68
Thickness at arch	1.2	1.2	1.7	2.2	2.7	2.9	3.2
Weight per 100 pce in kg approx.	0.50	0.50	0.80	1.70	3.30	4.90	7.20

Groove width for rope Ø	14	16	18	20	22	24	26
	13	15	16	18	20	22	24
Internal width	32	36	40	45	50	56	62
Internal height	51	58	64	72	80	90	99
Total length	83	90	92	110	120	130	153
Thickness at arch	3.5	3.8	4.2	5.2	5.2	6.2	6.5
Weight per 100 pce in kg approx.	11.30	14.80	19.10	29.80	33.00	43.50	59.10

Groove width for rope Ø	28	30	32	34	36	38	42
	26	28	30	32	34	36	40
Internal width	70	75	80	95	100	110	120
Internal height	112	120	128	152	160	176	192
Total length	167	186	195	225	230	236	276
Thickness at arch	7.3	8.0	8.0	8.0	8.0	8.5	10.5
Weight per 100 pce in kg approx.	84.00	99.00	105.80	117.90	133.10	218.40	323.20