

When ordering, specify:  
A = with eye bolt

C = with protruding bolt,  
nut and split pin (only  
available from size 0.4 up)

## No. 504 Zinc-plated shackles

to DIN 82101.

All dimensions in mm.



Nominal size	0.1	0.16	0.25	0.4	0.6	1	1.6
Bolt size	5	6	8	10	12	16	20
Internal height	15.5	18	24	30	36	49	61
Jaw width	7	8	11	14	17	21	27
Shackle thickness	4	5	7	8	10	13	17
Load capacity in kg	100	160	250	400	630	1000	1600
Weight in kg approx.	0.02	0.02	0.05	0.09	0.17	0.36	0.75



Nominal size	2	2.5	3	4	5	6	8
Bolt size	22	24	27	30	36	39	45
Internal height	67	73	83.5	91	111	119.5	139.5
Jaw width	30	33	38	42	47	53	60
Shackle thickness	19	21	24	27	30	34	38
Load capacity in kg	2000	2500	3150	4000	5000	6300	8000
Weight in kg approx.	1.00	1.32	1.85	2.50	4.00	5.40	7.90

Nominal size	10	12	16	20	25
Bolt size	48	52	60	68	72
Internal height	147	158	185	211	221
Jaw width	66	73	81	90	100
Shackle thickness	42	47	52	58	63
Load capacity in kg	10000	12500	16000	20000	25000
Weight in kg approx.	10.00	13.50	19.20	28.00	34.00