

No. 519 c Galvanized turnbuckles

acc. to DIN 1480 hook/hook.

All dimensions in mm.



Size of thread	M 6	M 8	M 10	M 12	M 14	M 16
Length of turnbuckle frame	110	110	125	125	140	170
Overall length	180 - 260	195 - 270	230 - 315	250 - 330	280 - 370	320 - 430
Hook opening width	8,5	11	13,5	15,5	18,5	19
Adjustable	80	75	85	80	90	110
Length of frame thread	12	15	18	21	24	27
Weight in kg about	0,10	0,17	0,30	0,44	0,67	0,95

Size of thread	M 20	M 22	M 24	M 30	M 36
Length of turnbuckle frame	200	220	255	255	295
Overall length	400 - 530	428 - 573	490 - 660	530 - 690	600 - 780
Hook opening width	20,5	26	26	33	44
Adjustable	130	145	170	160	180
Length of frame thread	34	37	39	45	55
Weight in kg about	1,75	2,40	3,22	4,88	8,27

No. 519 d Galvanized turnbuckles

acc. to DIN 1480 eye/eye.

All dimensions in mm.



Size of thread	M 6	M 8	M 10	M 12	M 14	M 16
Length of turnbuckle frame	110	110	125	125	140	170
Overall length	167 - 247	179 - 254	210 - 295	230 - 310	250 - 340	330 - 440
Inside diameter eye	9	10	14	16	18	22
Adjustable	80	75	85	80	90	110
Length of eye piece	80	84	105	115	122	165
Length of frame thread	12	15	18	21	24	27
Weight in kg about	0,10	0,16	0,27	0,41	0,60	1,00

Size of thread	M 20	M 22	M 24	M 30	M 36
Length of turnbuckle frame	200	220	255	255	295
Overall length	335 - 465	368 - 513	420 - 590	510 - 670	560 - 740
Inside diameter eye	24	27	27	31	37
Adjustable	130	145	170	160	180
Length of eye piece	167	167	205	255	276
Length of frame thread	34	37	39	45	55
Weight in kg about	1,54	2,00	2,70	4,35	7,25