

No. 519 c Zinc-plated turnbuckles

to DIN 1480 with hooks on both ends.
All dimensions in mm.



Thread diameter	M 6	M 8	M 10	M 12	M 14	M 16
Tension nut length	108	108	126	126	140	170
Total length	180 - 260	195 - 270	230 - 315	250 - 330	280 - 370	320 - 430
Jaw width	8	11	12	14	16	18
Tension travel	80	75	85	80	90	110
Nut thread length	12	15	18	21	24	27
Weight in kg approx.	0.10	0.19	0.28	0.42	0.55	1.00

Thread diameter	M 20	M 22	M 24	M 30
Tension nut length	200	215	245	255
Total length	400 - 530	428 - 573	490 - 660	530 - 690
Jaw width	20	24	24	28
Tension travel	130	145	170	160
Nut thread length	34	37	39	45
Weight in kg approx.	1.60	2.10	2.00	3.90

No. 519 d Zinc-plated turnbuckles

to DIN 1480 with eyes on both ends.
All dimensions in mm.



Thread diameter	M 6	M 8	M 10	M 12	M 14	M 16
Tension nut length	108	108	126	125	140	170
Total length	167 - 247	179 - 254	210 - 295	230 - 310	250 - 340	330 - 440
Eye hole Ø	9	10	14	16	18	22
Tension travel	80	75	85	80	90	110
Length of eye part	80	84	105	115	122	165
Nut thread length	12	15	18	21	24	27
Weight in kg approx.	0.10	0.14	0.28	0.42	0.55	1.00

Thread diameter	M 20	M 22	M 24	M 30
Tension nut length	200	215	245	255
Total length	335 - 465	368 - 513	420 - 590	510 - 670
Eye hole Ø	24	28	28	31
Tension travel	130	145	170	160
Length of eye part	167	167	205	255
Nut thread length	34	37	39	45
Weight in kg approx.	1.60	2.10	2.00	3.90