

No. 539 A Zinc-plated quick links

to **DIN 56927**, with union nut, small opening, load capacity punched in, tenfold safety factor, for theatre engineering and stage operations.
All dimensions in mm.



Material thickness	4	5	6	8	10	12
Internal width	11.5	13	14.5	17.5	20.5	23.5
Internal height	31.5	39.5	45	58	69	80.5
Threaded nut height	12.5	16	19	24	29	33
Opening width	5.5	6.5	7.5	11	12	15
Load capacity in kg	90	140	200	350	550	750
Weight per 100 pce in kg approx.	1.18	2.05	3.50	7.85	14.56	23.47

No. 539 B Zinc-plated quick links

to **DIN 56927**, with union nut, large opening, load capacity punched in, tenfold safety factor, for theatre engineering and stage operations.
All dimensions in mm.



Material thickness	4	5	6	8	10	12
Internal width	11.5	13	14.5	17.5	20.5	23.5
Internal height	45	52	58.5	72	85.5	100
Threaded nut height	19	22	25	31.5	36	43
Opening width	11.5	13	14.5	17.5	20.5	23.5
Load capacity in kg	90	140	200	350	550	750
Weight per 100 pce in kg approx.	1.50	2.50	4.30	11.00	17.20	27.50