

When ordering, specify:
 A = untreated
 B = drilled

No. 544 Solid thimbles

to **DIN 3091**. Material: nominal size 8 - 36 made of GTW 40 DIN 1692, nominal size 40 - 80 made of GGG 40 DIN 1693, nominal size 8 - 14 without recess.
 All dimensions in mm.



Nominal size	8	10	12	14	16	18	20
Groove width	9	11	13	16	18	20	22
Thimble thickness	15	17.5	20	23.5	26	28.5	31
Width	40	50	60	70	80	90	100
Total length	66	82	98	114	130	145	161
Unmachined hole	14	18	21	25	28	31	35
Max. hole size	20	25	30	35	40	45	50
Weight in kg approx.	0.20	0.30	0.50	0.70	0.80	1.10	1.40

Nominal size	22	24	26	28	32	36	40
Groove width	24	26	29	31	35	40	44
Thimble thickness	33.5	36	39.5	42	47	53	58
Width	110	120	130	140	160	180	200
Total length	177	193	209	224	256	288	320
Unmachined hole	38	41	44	47	53	59	65
Max. hole size	55	60	65	70	80	90	100
Weight in kg approx.	1.80	2.30	3.00	3.70	5.30	7.50	10.40

Nominal size	44	48	52	56	64	72	80
Groove width	48	53	57	62	70	79	88
Thimble thickness	63	69	74	80	90	101	112
Width	220	240	260	280	320	360	400
Total length	352	384	416	448	512	576	640
Unmachined hole	70	76	81	86	95	104	112
Max. hole size	110	120	130	140	160	180	200
Weight in kg approx.	13.40	17.80	23.10	29.00	41.30	66.00	99.00

We are unable to assume warranty if the thimble holes are drilled larger than stated under max. hole size due to customer request.