

High-strength shackles straight D

When ordering, specify:
A = with eye bolt

B = with protruding bolt,
nut and split pin

No. 550 High-strength straight D shackles to EN 13889

zinc-plated, bolt and shackle eyes painted pale blue. Load capacity, nominal size, batch and "CE" sign punched in. All dimensions in mm.



Nominal size	0.5	0.75	1	1.5	2	3.25	4.75
Load capacity in kg	500	750	1000	1500	2000	3250	4750
Shackle thickness	6.5	8	10	11	13	16	19
Internal height	23	26	31	36	41	51	60
Jaw width	13	13	16	18	21	27	32
Bolt size	8	10	11	13	16	19	22
External Ø, bolt retainer	17	21	25	27	30	40	48
Weight, version A in kg approx.	0.10	0.10	0.10	0.20	0.30	0.50	0.90
Weight, version B in kg approx.	0.10	0.10	0.20	0.20	0.30	0.60	1.00



Nominal size	6.5	8.5	9.5	12	13.5	17	25
Load capacity in kg	6500	8500	9500	12000	13500	17000	25000
Shackle thickness	22	25	29	32	35	38	44
Internal height	71	81	90	100	113	124	146
Jaw width	36	43	46	52	57	60	73
Bolt size	25	29	32	35	38	41	51
External Ø, bolt retainer	54	60	67	76	84	92	110
Weight, version A in kg approx.	1.4	2	2.8	4.1	5.2	7.1	11.6
Weight, version B in kg approx.	1.5	2.3	3.1	4.7	6.1	7.8	13.1