

### No. 750 Folding gate runners for manually operated steel gates

with thrust ball bearing above the nut, steel bracket with welded spindle made of bright drawn round steel, zinc-plated. The runners are equipped with hardened special steel sheaves with cone ball bearings (nominal size 1 and 8 with two precision ball bearings), protection from dust and water for smooth, quiet running. All dimensions in mm.



Nominal size	1	2	3	4	5	6	7	8
D	35	45	45	45	45	45	45	39
G	16	16	20	22	23	23	26	23
a	9	13	13	13	13	13	13	13
c	3.5	2.5	2.5	2.5	2.5	2.5	2.5	2
d	45	54	54	54	54	54	58	53
d1	50	62	62	62	62	62	67	62
e	9.5	11	11	11	11	11	11	9.5
f	38	42	42	42	42	42	52	53
g	314	380	380	380	380	340	390	380
h	50	70	70	70	70	70	70	80
i	16.5	16.5	19.5	22	22	22	27	22
k	10	10	10	10	10	10	15	16
l	28	47	47	47	47	47	35	50
m	8	10	10	10	10	10	10	12
n max.	35	40	40	40	40	40	45	35
o	65	77.5	76.5	77.5	76.5	78.5	79.5	72.5
q	205	250	250	250	250	210	250	250
s	65	65	65	65	65	65	65	70
t	12	12	13	15	15	15.5	15.5	15.5
u	38	38	38	38	38	38	48	40
w	106	130	130	130	130	130	140	130
Thread diameter M	M 16	M 16	M 20	M 22	M 22	M 22	M 27	M 22
Load capacity/piece in kg	120	200	250	350	350	350	500	700
Weight in kg approx.	1.11	1.73	1.98	2.21	2.26	2.14	3.27	2.87

