

No. 75 Electric gin block with rope and load pressure brake

lightweight and compact design. With its bracket and hook interlock, the gin block can easily be installed on swivel booms. The load automatically stops when the limiting arm is touched by the hook plate. Thanks to the two brake systems (dynamic and mechanical) the braking effect is immediately and securely activated.

Our electric gin block features the following technical properties:

- 5 m power cable
- 10 m control cable (to remote control)
- automatic motor switch-off when rope is fully wound
- fully equipped and ready for operation, with rope hook and safety hook
- 360° rotating hook with safety latch
- IP 65 controller, with emergency stop
- IP 44 motor protection rating

On request we can provide the following optional extras:

- 180° swivel-mounted support arm with 250 kg load capacity
- 180° swivel-mounted support arm with 600 kg load capacity
- control cable extension

All dimensions in mm.



Load capacity at all rope positions in kg	80	160	230	300
Rope speed at full load m/min	18-30	15-22	9-14	9-13
Motor data 230 V	0.8 kW/4 A	1.2 kW/6.0 A	1.3 kW/6.5 A	1.5 kW/7.5 A
Lifting height in m	23	30	24	24
Rope diameter	4	5	5	5
Weight in kg	18.00	23.00	24.00	25.00
A	200	244	244	244
B	104	115	115	115
C	168	182	182	182
D	605	640	640	640
E	266	280	280	280
F	339	360	360	360
G	270	285	285	285

